

# External PTZ Camera Specification



Robust vehicle ready IP66 external camera with 50m IR. Continuous 360 degree rotation, IR cut filter, 36X optical and 32X digital zoom with selectable protocols, this hi resolution camera is ideal for all kinds of vehicle installations.



**EXTPTZIRCAM**



Image Sensor	1/4 " Super HAD II CCD ( Double Scan )
Total Pixels	NTSC: 1028 ( H )x508 ( V ) PAL: 1028 ( H )x596 ( V )
Lens	Optical 36x, Digital 32x, f=3.4 to 122.4mm (F1.6 to 4.5)
Scanning System	Interlace
Synchronisation	Internal
Frequency	NTSC: 15.734 Khz(H), 59.94 Hz(V) PAL: 15.625 Khz(H), 50.00 Hz(V)
Resolution	700 TV Lines ( Colour ) / 800 TV Lines ( BW )
Min Illumination	Colour: 0.5Lux, BW: 0.2 Lux
S/N ( Y Signal )	50 dB
Video Output	1.0Vp-p / 75 Ohms, Composite
Focus	Auto / Manual / One-Push / Infinity
Focus Distance	0.1 / 1.3 / 1.8 / 3.0 / 5.0m
E.Zoom	Off / Max 2x-32x
Exposure	Auto / Shutter PRI / Manual
Day and Night	Auto / Day / Night
Gain Control	Off / On ( Auo Max 32 dB )
White Balance	1,800 K to 10,500 K
Image Stabiliser	On/Off
Image DNR	Off / Manual / Auto
Privacy Mask	Off / 8 zones
Display	Disp Sel / Init Sel, Set Tilt / Set Init Msg / Language

# External PTZ Camera Specification



**EXTPTZIRCAM**



Shutter Speed

NTSC: 1/60 - 1/100,000 sec

PAL: 1/50 - 1/100.000 sec

WDR / BLC

Off / WDR / BLC

Communication

Baud Rate: 2400, 4800, 6900, 38400, 57600, 115200 bps

Protocol: WTX, PELCO-D V1, PELCO-P, PELCO-D V5

Size

138(Ø) x 212 (H)